




**华亚东营塑胶有限公司**  
**产品检验报告/质量合格证**

编号：HYDY/JLA-C05/015070503AD-B

第 1 页 / 共 1 页

委托单位	华亚东营塑胶有限公司生产一课	品牌	华刚牌	标志																																																	
样品名称	PVC-U 农灌管	规格型号	110mm×2.2mm																																																		
样品编号	015070503AD-B	样品状态	颜色为灰色、外表光滑、截面平整无缺陷，数量满足试验要求																																																		
生产日期	2015.07.05~2015.07.05	收样日期	2015.07.05																																																		
检验日期	2015.07.06~2015.07.07	检验依据	GB/T 13664-2006																																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">检验项目</th> <th style="width: 25%;">技术指标</th> <th style="width: 25%;">检验结果</th> <th style="width: 25%;">单项判定</th> </tr> </thead> <tbody> <tr> <td>外观</td> <td>无缺陷</td> <td>视其外观无缺陷</td> <td>合格</td> </tr> <tr> <td>颜色</td> <td>灰色</td> <td>灰色</td> <td>合格</td> </tr> <tr> <td>平均外径mm</td> <td>110.0~110.4</td> <td>110.2</td> <td>合格</td> </tr> <tr> <td>壁厚mm</td> <td>2.2~2.6</td> <td>2.3</td> <td>合格</td> </tr> <tr> <td>不圆度mm</td> <td>≤2.2</td> <td>0.1</td> <td>合格</td> </tr> <tr> <td>弯曲度%</td> <td>≤1.0</td> <td>0.2</td> <td>合格</td> </tr> <tr> <td>长度 mm</td> <td>≥6000</td> <td>6020</td> <td>合格</td> </tr> <tr> <td>水压试验 (20℃、4 倍公称压力)</td> <td>持压 1h 无破裂、无渗漏</td> <td>1.28MPa 持压 1h 无破裂、无渗漏</td> <td>合格</td> </tr> <tr> <td>扁平试验 (压至 50%)</td> <td>不破裂</td> <td>不破裂</td> <td>合格</td> </tr> <tr> <td>纵向回缩率 %</td> <td>≤5</td> <td>1.3</td> <td>合格</td> </tr> <tr> <td>环刚度/ (KN/m<sup>2</sup>)</td> <td>≥2.0</td> <td>2.5</td> <td>合格</td> </tr> </tbody> </table>						检验项目	技术指标	检验结果	单项判定	外观	无缺陷	视其外观无缺陷	合格	颜色	灰色	灰色	合格	平均外径mm	110.0~110.4	110.2	合格	壁厚mm	2.2~2.6	2.3	合格	不圆度mm	≤2.2	0.1	合格	弯曲度%	≤1.0	0.2	合格	长度 mm	≥6000	6020	合格	水压试验 (20℃、4 倍公称压力)	持压 1h 无破裂、无渗漏	1.28MPa 持压 1h 无破裂、无渗漏	合格	扁平试验 (压至 50%)	不破裂	不破裂	合格	纵向回缩率 %	≤5	1.3	合格	环刚度/ (KN/m <sup>2</sup> )	≥2.0	2.5	合格
检验项目	技术指标	检验结果	单项判定																																																		
外观	无缺陷	视其外观无缺陷	合格																																																		
颜色	灰色	灰色	合格																																																		
平均外径mm	110.0~110.4	110.2	合格																																																		
壁厚mm	2.2~2.6	2.3	合格																																																		
不圆度mm	≤2.2	0.1	合格																																																		
弯曲度%	≤1.0	0.2	合格																																																		
长度 mm	≥6000	6020	合格																																																		
水压试验 (20℃、4 倍公称压力)	持压 1h 无破裂、无渗漏	1.28MPa 持压 1h 无破裂、无渗漏	合格																																																		
扁平试验 (压至 50%)	不破裂	不破裂	合格																																																		
纵向回缩率 %	≤5	1.3	合格																																																		
环刚度/ (KN/m <sup>2</sup> )	≥2.0	2.5	合格																																																		
总判定																																																					

批准： 

审核： 

编制： 

地址：山东省东营市东二路 251 号  
电话：0546-8305238  
邮政编码：257091

传真：0546-8307178  
E-mail:huaya@hydyplst.com.cn  
http://www.hydyplst.com.cn